

PRODUCT SPECIFICATION

		Grade Availability by GSM							Units	Tolerance	
GSM		54	58	60	64	70	80	90	100	g/m²	±2.5%
Bulk		1.40	1.35	1.35	1.32	1.30	1.25	1.25	1.25	cc/gm	min.
Cobb		25							g/m²	max.	
Brightness		94							% ISO	±1	
Opacity		91	92	92	92	93	94	94	94	%	±1
Wax Pick		14A							no.	min.	
Breaking Length	MD	5500	5500	5500	5500	5500	5200	5200	5200	mtr	±200
	CD	2700	2700	2700	2700	2700	2500	2500	2500		
Tear Factor	MD	50							-	min.	
	CD	60									
Bendsten Smoothness	TOP	120-160							ml/min	max.	
	BOTTOM	140-180									

PACKING INFORMATION

REELS

Width: 210-2200 mm
Core Inner Dia: 76 mm/ 3"

SHEETS

Min. Size: 390 x 510 mm
Max. Size: 900 x 1350 mm

PALLETS

Min. Height: 1100 mm
Max. Height: 1300 mm

DECKLE

4400 mm

For more information, please contact your Khanna Paper Mills representative or visit our website at www.khannapaper.com

This information is subject to modification without notification.