

PRODUCT SPECIFICATION

		Grade Availability by GSM						Units	Tolerance	
GSM		48	50	52	54	56	58	60	g/m²	±2.5%
Bulk		1.40	1.40	1.40	1.40	1.40	1.38	1.38	cc/gm	min.
Cobb		25						g/m²	max.	
Brightness		88						% ISO	min.	
Opacity		90	91	91	93	93	93	93	%	±1
Wax Pick		12A						no.	min.	
Breaking Length	MD	4800	5000	5000	5200	5200	5200	5200	mtr	±200
	CD	1900	2000	2000	2100	2100	2100	2100		
Tear Factor	MD	55						-	min.	
	CD	65								
Bendtsen Smoothness	TOP	130-160						ml/min	max.	
	BOTTOM	140-180								

PACKING INFORMATION			DECKLE
REELS	Width: 220 - 1800 mm	Core Inner Dia: 76 mm/3"	6450 mm

For more information, please contact your Khanna Paper Mills representative or visit our website at www.khannapaper.com
This information is subject to modification without notification.

PRODUCT SPECIFICATION

		Grade Availability by GSM						Units	Tolerance	
GSM		58	60	64	70	80	90	100	g/m²	±2.5%
Bulk		1.28	1.28	1.28	1.25	1.23	1.23	1.23	cc/gm	min.
Cobb		25						g/m²	max.	
Brightness		88						% ISO	±1	
Opacity		92	92	92	93	94	94	94	%	±1
Wax Pick		14A						no.	min.	
Breaking Length	MD	5200	5200	5200	5200	5000	5000	5000	mtr	±200
	CD	2300	2300	2300	2300	2100	2100	2100		
Tear Factor	MD	50						-	min.	
	CD	60								
Bendsten Smoothness	TOP	140-180						ml/min	max.	
	BOTTOM	160-200								

PACKING INFORMATION

REELS

Width: 210-2200 mm

Core Inner Dia: 76 mm/ 3"

SHEETS

Min. Size: 390 x 510 mm

Max. Size: 900 x 1350 mm

PALLETS

Min. Height: 1100 mm

Max. Height: 1300 mm

DECKLE

4400 mm

For more information, please contact your Khanna Paper Mills representative or visit our website at www.khannapaper.com
This information is subject to modification without notification.