

PRODUCT SPECIFICATION

|                     |        | Grade Availability by GSM |      |      |      |      |      |      | Units            | Tolerance |
|---------------------|--------|---------------------------|------|------|------|------|------|------|------------------|-----------|
| GSM                 |        | 48                        | 50   | 52   | 54   | 56   | 58   | 60   | g/m <sup>2</sup> | ±2.5%     |
| Bulk                |        | 1.40                      | 1.40 | 1.40 | 1.40 | 1.40 | 1.38 | 1.38 | cc/gm            | min.      |
| Cobb                |        | 25                        |      |      |      |      |      |      | g/m <sup>2</sup> | max.      |
| Brightness          |        | 82                        |      |      |      |      |      |      | % ISO            | ±1        |
| Opacity             |        | 90                        | 91   | 91   | 92   | 92   | 93   | 93   | %                | ±1        |
| Wax Pick            |        | 12A                       |      |      |      |      |      |      | no.              | min.      |
| Breaking Length     | MD     | 4800                      | 4800 | 4800 | 5000 | 5000 | 4800 | 4800 | mtr              | ±200      |
|                     | CD     | 1900                      | 1900 | 1900 | 2100 | 2100 | 2000 | 2000 |                  |           |
| Tear Factor         | MD     | 50                        |      |      |      |      |      |      | -                | min.      |
|                     | CD     | 60                        |      |      |      |      |      |      |                  |           |
| Bendtsen Smoothness | TOP    | 130-160                   |      |      |      |      |      |      | ml/min           | max.      |
|                     | BOTTOM | 140-180                   |      |      |      |      |      |      |                  |           |

| PACKING INFORMATION |                      |                          | DECKLE  |
|---------------------|----------------------|--------------------------|---------|
| REELS               | Width: 220 - 1800 mm | Core Inner Dia: 76 mm/3" | 6450 mm |

For more information, please contact your Khanna Paper Mills representative or visit our website at [www.khannapaper.com](http://www.khannapaper.com)

This information is subject to modification without notification.